

Package ‘journalR’

December 19, 2025

Type Package

Title Formatting Tools for Scientific Journal Writing

Version 0.6.0

Maintainer Sam Byrne <ssbyrne@uw.edu>

Description Scientific journal numeric formatting policies implemented in code. Emphasis on formatting mean/upper/lower sets of values to pasteable text for journal submission. For example `c(2e6, 1e6, 3e6)` becomes `"`2.00 million (1.00--3.00)"`. Lancet and Nature have built-in styles for rounding and punctuation marks. Users may extend journal styles arbitrarily. Four metrics are supported; proportions, percentage points, counts and rates. Magnitudes for all metrics are discovered automatically.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.2.0)

Imports checkmate, data.table, glue

Suggests devtools (>= 2.4.5), testthat (>= 3.0.0)

Config/testthat/edition 3

RoxygenNote 7.3.2

URL <https://github.com/epi-sam/journalR>

BugReports <https://github.com/epi-sam/journalR/issues>

NeedsCompilation no

Author Sam Byrne [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0008-1067-307X>>)

Repository CRAN

Date/Publication 2025-12-19 09:50:11 UTC

Contents

en_dash	2
fmt_magnitude	3
format_journal_clu	4
format_journal_df	5
format_lancet_clu	7
format_lancet_df	8
format_metric_cols	9
format_nature_clu	10
format_nature_df	11
format_oxford_comma	13
fround	13
fround_metric	14
fround_metric_lancet	15
get_metrics	16
get_metric_labels	16
get_style	17
get_style_schema	18
mid_dot	18
new_style	19
set_magnitude	21
set_style	22
style_lancet	23
style_nature	24
thin_space	24
Index	26

en_dash	<i>En-dash</i>
---------	----------------

Description

Standard for "x – y" and Lancet negative: ("U2013")

Usage

en_dash()

Value

[chr] en-dash character

See Also

Other marks: [mid_dot\(\)](#), [thin_space\(\)](#)

Examples

```
en_dash()
```

fmt_magnitude	<i>Format magnitude</i>
---------------	-------------------------

Description

Format a numeric vector into a string with specified magnitude (billion, million, thousand).

Usage

```
fmt_magnitude(  
  x,  
  metric,  
  rate_unit = NULL,  
  digits = 1,  
  nsmall = 1,  
  decimal.mark = ".",  
  big.mark = ",",  
  mag = NULL,  
  count_label_thousands = FALSE  
)
```

Arguments

x	[num] numeric vector
metric	[chr 'c("prop", "pp", "count", "rate")']
rate_unit	[chr: default NULL] unit label for rates (e.g., "deaths", "cases"). Required when metric = "rate", ignored otherwise.
digits	[int: default 1L] passed to 'round()'
nsmall	[int: default 1L] passed to 'format()'
decimal.mark	[chr: default "."] decimal mark passed to 'format()'
big.mark	[chr: default ","] thousands separator passed to 'format()'
mag	[chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b"
count_label_thousands	[lgl: default FALSE] allow thousands magnitude? Not Lancet-valid. Passed to 'set_magnitude()'

Details

Unaware of styles, just a hard-coded git-er-done function.

Caution - thousands magnitude is not Lancet compliant.

Value

[chr] formatted string

See Also

Other vector_formats: [add_epsilon\(\)](#), [format_oxford_comma\(\)](#), [fround\(\)](#), [fround_count_rate\(\)](#), [fround_metric\(\)](#), [fround_metric_lancet\(\)](#), [fround_props\(\)](#)

Other magnitudes: [set_magnitude\(\)](#), [set_magnitude_count\(\)](#), [set_magnitude_prop\(\)](#), [set_magnitude_rate\(\)](#)

Examples

```
fmt_magnitude(123456789, metric = "count")
fmt_magnitude(0.0000123, metric = "rate", rate_unit = "deaths")
```

format_journal_clu *Format central, lower, upper value triplets for journal presentation*

Description

Defaults are generic. This function allows special formatting marks to be applied by journal. Use 'format_lancet_clu()' for Lancet-specific formatting. Use 'format_nature_clu()' for Nature-specific formatting.

Usage

```
format_journal_clu(
  central,
  lower,
  upper,
  metric,
  rate_unit = NULL,
  mag = NULL,
  style_name = "nature"
)
```

Arguments

central	[num] central, point_estimate value vector
lower	[num] lower bound vector
upper	[num] upper bound vector
metric	[chr c(prop, pp, count, rate)] metric - proportion, percentage point, count, or rate
rate_unit	[chr: default NULL] rate unit label (required when metric = 'rate')
mag	[chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b" - Examples: "deaths", "cases", "events", "births"
style_name	[chr: default 'nature'] style name - controls rounding and formatting.

Details

Takes three vectors as main arguments for data.table-friendly vectorization.

‘central’ could be mean, median, point_estimate

Transform `c(central = 0.994, lower = 0.984, upper = 0.998)` to "99.4% (98.4–99.8)"

Accounts for negative values, and UIs that cross zero. Checks if central, lower, upper values are in the correct order.

Value

[chr] formatted string vector

See Also

Other styled_formats: [format_journal_df\(\)](#), [format_lancet_clu\(\)](#), [format_lancet_df\(\)](#), [format_metric_cols\(\)](#), [format_nature_clu\(\)](#), [format_nature_df\(\)](#), [fround_clu_triplet\(\)](#), [new_style\(\)](#)

Examples

```
format_journal_clu(
  central = c(0.994, -0.994)
  , lower = c(0.984, -0.998)
  , upper = c(0.998, -0.984)
  , metric = "prop"
)

# Rate formatting with rate_unit
format_journal_clu(
  central = 0.0000123,
  lower = 0.0000098,
  upper = 0.0000152,
  metric = "rate",
  rate_unit = "deaths"
)
```

format_journal_df	<i>Return a table with formatted central, lower, upper</i>
-------------------	--

Description

Assumes a single data-type (metric) for the whole table (e.g. 'prop', 'pp', 'count')

Usage

```
format_journal_df(
  df,
  metric,
  new_var = "clu_fmt",
```

```

    style_name = "nature",
    central_var = "mean",
    lower_var = "lower",
    upper_var = "upper",
    remove_clu_columns = TRUE,
    rate_unit = NULL,
    mag = NULL
  )

```

Arguments

df	[data.frame, data.table]
metric	[chr c('prop', 'pp', 'count', 'rate')] a single metric
new_var	[chr: default 'clu_fmt'] name of new formatted column
style_name	[chr: default 'nature'] style name - controls rounding and formatting.
central_var	[chr: default 'mean'] name of central tendency variable
lower_var	[chr: default 'lower'] name of lower bound variable
upper_var	[chr: default 'upper'] name of upper bound variable
remove_clu_columns	[lgl: default TRUE] remove central, lower, upper variables after formatting?
rate_unit	[chr: default NULL] rate unit label (required when metric = 'rate') - Examples: "deaths", "cases", "events", "births"
mag	[chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b" - Examples: "deaths", "cases", "events", "births"

Value

[data.frame] data.frame, data.table with new 'clu_fmt' column

See Also

Other styled_formats: [format_journal_clu\(\)](#), [format_lancet_clu\(\)](#), [format_lancet_df\(\)](#), [format_metric_cols\(\)](#), [format_nature_clu\(\)](#), [format_nature_df\(\)](#), [fround_clu_triplet\(\)](#), [new_style\(\)](#)

Examples

```

df <- data.frame(
  location_id = c(1, 2, 3)
  , mean      = c(0.1234, 0, -0.3456)
  , lower     = c(0.1134, -0.2245, -0.4445)
  , upper     = c(0.1334, 0.2445, 0.3556)
)
format_journal_df(df, metric = "prop")

```

```
# Rate formatting example
rate_df <- data.frame(
  location = c("Global", "USA"),
  mean     = c(0.0000123, 0.0000456),
  lower    = c(0.0000098, 0.0000401),
  upper    = c(0.0000152, 0.0000512)
)
format_journal_df(rate_df, metric = "rate", rate_unit = "deaths")
```

format_lancet_clu	<i>Format central, lower, upper value triplets for Lancet journal presentation</i>
-------------------	--

Description

Format central, lower, upper value triplets for Lancet journal presentation

Usage

```
format_lancet_clu(central, lower, upper, metric, rate_unit = NULL, mag = NULL)
```

Arguments

central	[num] central, point_estimate value vector
lower	[num] lower bound vector
upper	[num] upper bound vector
metric	[chr c(prop, pp, count, rate)] metric - proportion, percentage point, count, or rate
rate_unit	[chr: default NULL] rate unit label (required when metric = 'rate')
mag	[chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b" - Examples: "deaths", "cases", "events", "births"

Value

[chr] formatted string vector

See Also

Other styled_formats: [format_journal_clu\(\)](#), [format_journal_df\(\)](#), [format_lancet_df\(\)](#), [format_metric_cols\(\)](#), [format_nature_clu\(\)](#), [format_nature_df\(\)](#), [fround_clu_triplet\(\)](#), [new_style\(\)](#)

Examples

```

format_lancet_clu(
  central = c(0.994, -0.994)
  , lower = c(0.984, -0.998)
  , upper = c(0.998, -0.984)
  , metric = "prop"
)

# Rate example with Lancet formatting
format_lancet_clu(
  central = 0.0000123,
  lower   = 0.0000098,
  upper   = 0.0000152,
  metric  = "rate",
  rate_unit = "deaths"
)

```

format_lancet_df	<i>Return a table with formatted central, lower, upper for Lancet journal</i>
------------------	---

Description

Assumes a single data-type (metric) for the whole table (e.g. 'prop', 'pp', 'count')

Usage

```

format_lancet_df(
  df,
  metric,
  new_var = "clu_fmt",
  central_var = "mean",
  lower_var = "lower",
  upper_var = "upper",
  remove_clu_columns = TRUE,
  rate_unit = NULL,
  mag = NULL
)

```

Arguments

df	[data.table] with central, lower, upper columns
metric	[chr c('prop', 'pp', 'count', 'rate')] metric - proportion, percentage point, count, or rate
new_var	[chr: default 'clu_fmt'] name of new formatted column
central_var	[chr: default 'mean'] name of central tendency e.g. 'point_estimate'
lower_var	[chr: default 'lower']

upper_var [chr: default 'upper']
 remove_clu_columns [lgl: default TRUE] remove central, lower, upper columns after formatting?
 rate_unit [chr: default NULL] rate unit label (required when metric = 'rate')
 mag [chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b" - Examples: "deaths", "cases", "events", "births"

Value

[data.frame, data.table] with mean_95_UI_formatted column, and central, lower, upper columns removed (if specified)

See Also

Other styled_formats: [format_journal_clu\(\)](#), [format_journal_df\(\)](#), [format_lancet_clu\(\)](#), [format_metric_cols\(\)](#), [format_nature_clu\(\)](#), [format_nature_df\(\)](#), [fround_clu_triplet\(\)](#), [new_style\(\)](#)

Examples

```
df <- data.frame(
  location_id = 1
  , location_name = "Global"
  , me_name = "vacc_dpt1"
  , mean = 55.8e6
  , lower = 50.7e6
  , upper = 60.7e6
)
format_lancet_df(df = df, metric = "count", central_var = 'mean')
```

format_metric_cols *Format multiple data.frame 'mean_*' columns for presentation (by metric).*

Description

Format one or more 'mean_' columns by magnitude, metric, and style.

Usage

```
format_metric_cols(
  df,
  metric,
  var_prefix = "mean",
  rate_unit = NULL,
  mag = NULL,
```

```

    style_name = "nature"
  )

```

Arguments

df [data.table] input data.table with one or more 'mean_' columns

metric [chr c('prop', 'pp', 'count', 'rate')] a single metric

var_prefix [chr: default 'mean'] prefix of mean variable names to format. Implemented as e.g. "^mean[_]+" to capture 'mean', 'mean_1990', 'mean_2000', etc.

rate_unit [chr: default NULL] unit label for rates (e.g., "deaths", "cases"). Required when metric = "rate", ignored otherwise.

mag [chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b"

style_name [chr: default 'nature'] style name - controls rounding and formatting.

Value

[data.table] copy of input data.table with formatted mean column(s)

See Also

Other styled_formats: [format_journal_clu\(\)](#), [format_journal_df\(\)](#), [format_lancet_clu\(\)](#), [format_lancet_df\(\)](#), [format_nature_clu\(\)](#), [format_nature_df\(\)](#), [fround_clu_triplet\(\)](#), [new_style\(\)](#)

Examples

```

df <- data.frame(
  location_id = c(1, 2, 3)
  , mean_1990 = c(100, 1e6, 1e9)
  , mean_2000 = c(200, 2e6, 2e-1)
)
format_metric_cols(df, metric = "count")

```

format_nature_clu	<i>Format central, lower, upper value triplets for Nature journal presentation</i>
-------------------	--

Description

Format central, lower, upper value triplets for Nature journal presentation

Usage

```
format_nature_clu(central, lower, upper, metric, rate_unit = NULL, mag = NULL)
```

Arguments

central	[num] central, point_estimate value vector
lower	[num] lower bound vector
upper	[num] upper bound vector
metric	[chr c(prop, pp, count, rate)] metric - proportion, percentage point, count, or rate
rate_unit	[chr: default NULL] rate unit label (required when metric = 'rate')
mag	[chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b" - Examples: "deaths", "cases", "events", "births"

Value

[chr] formatted string vector

See Also

Other styled_formats: [format_journal_clu\(\)](#), [format_journal_df\(\)](#), [format_lancet_clu\(\)](#), [format_lancet_df\(\)](#), [format_metric_cols\(\)](#), [format_nature_df\(\)](#), [fround_clu_triplet\(\)](#), [new_style\(\)](#)

Examples

```
format_nature_clu(
  central = c(0.994, -0.994)
  , lower = c(0.984, -0.998)
  , upper = c(0.998, -0.984)
  , metric = "prop"
)

# Rate example with Nature formatting
format_nature_clu(
  central = 0.0000123,
  lower = 0.0000098,
  upper = 0.0000152,
  metric = "rate",
  rate_unit = "cases"
)
```

format_nature_df *Return a table with formatted central, lower, upper for Nature journal*

Description

Return a table with formatted central, lower, upper for Nature journal

Usage

```
format_nature_df(
  df,
  metric,
  new_var = "clu_fmt",
  central_var = "mean",
  lower_var = "lower",
  upper_var = "upper",
  remove_clu_columns = TRUE,
  rate_unit = NULL,
  mag = NULL
)
```

Arguments

df	[data.table]
metric	[chr c('prop', 'pp', 'count', 'rate')] a single metric
new_var	[chr: default 'clu_fmt'] name of new formatted column
central_var	[chr: default 'mean'] name of central tendency variable
lower_var	[chr: default 'lower'] name of lower bound variable
upper_var	[chr: default 'upper'] name of upper bound variable
remove_clu_columns	[lgl: default TRUE] remove central, lower, upper columns after formatting?
rate_unit	[chr: default NULL] rate unit label (required when metric = 'rate')
mag	[chr: default NULL] magnitude override - see set_magnitude() - For props/pp: "as-is" (no scaling, use values as provided) - For counts: "t" (thousand), "m" (million), "b" (billion) - For rates: "per10", "per100", "per1k", ..., "per10b" - Examples: "deaths", "cases", "events", "births"

Value

[data.table] copy of input data.table with new 'clu_fmt' column

See Also

Other styled_formats: [format_journal_clu\(\)](#), [format_journal_df\(\)](#), [format_lancet_clu\(\)](#), [format_lancet_df\(\)](#), [format_metric_cols\(\)](#), [format_nature_clu\(\)](#), [fround_clu_triplet\(\)](#), [new_style\(\)](#)

Examples

```
df <- data.frame(
  location_did = 1
  , location_name = "Global"
  , me_name = "vacc_dpt1"
  , mean = 55.8e6
  , lower = 50.7e6
)
```

```

    , upper      = 60.7e6
  )
  format_nature_df(df = df, metric = "count", central_var = 'mean')

```

format_oxford_comma *Format vector of items with Oxford comma*

Description

Format vector of items with Oxford comma

Usage

```
format_oxford_comma(vec, sep = "and")
```

Arguments

vec [any] vector of items to format
 sep [chr: default "and"] separator before last item

Value

[chr] formatted string with Oxford comma

See Also

Other vector_formats: [add_epsilon\(\)](#), [fmt_magnitude\(\)](#), [fround\(\)](#), [fround_count_rate\(\)](#), [fround_metric\(\)](#), [fround_metric_lancet\(\)](#), [fround_props\(\)](#)

Examples

```

format_oxford_comma(1:2)
format_oxford_comma(1:3)
format_oxford_comma(1:3, "or")

```

fround *Format and round*

Description

Unaware of data-type or schema, just a hard-coded git-er-done function.

Usage

```
fround(x, digits = 1L, nsmall = 1L, decimal.mark = ".")
```

Arguments

x	[num] numeric vector
digits	[integer] passed to 'round()'
nsmall	[integer] passed to 'format()'
decimal.mark	[chr] passed to 'format()'

Value

[chr] formatted string

See Also

Other vector_formats: [add_epsilon\(\)](#), [fmt_magnitude\(\)](#), [format_oxford_comma\(\)](#), [fround_count_rate\(\)](#), [fround_metric\(\)](#), [fround_metric_lancet\(\)](#), [fround_props\(\)](#)

Examples

```
fround(0.123456789)
fround(0.123456789, digits = 3)
fround(0.123456789, digits = 3, nsmall = 4)
```

fround_metric	<i>Format and round with data-type suffix</i>
---------------	---

Description

Unaware of schema, just a hard-coded git-er-done function.

Usage

```
fround_metric(x, metric = "prop", digits = 1L, nsmall = 1L, decimal.mark = ".")
```

Arguments

x	[num] numeric value
metric	[chr: default 'prop' c('prop', 'pp', 'count', 'rate')]
digits	[integer: default 1L] passed to 'round()'
nsmall	[integer: default 1L] passed to 'format()'
decimal.mark	[chr: default "."] decimal mark passed to 'format()'

Value

[chr] formatted string

See Also

Other vector_formats: [add_epsilon\(\)](#), [fmt_magnitude\(\)](#), [format_oxford_comma\(\)](#), [fround\(\)](#), [fround_count_rate\(\)](#), [fround_metric_lancet\(\)](#), [fround_props\(\)](#)

Examples

```
fround_metric(0.123456789)
fround_metric(0.123456789, 'pp', 3, 4)
fround_metric(c(55.8346, 123.456789), 'count', 3, 4, ".")
```

fround_metric_lancet *Format and round with data-type suffix*

Description

Lancet-specific wrapper for ‘fround_metric()’, using mid-dot as decimal mark. Retaining for legacy purposes (no Nature equivalent)

Usage

```
fround_metric_lancet(
  x,
  metric = "prop",
  digits = 1L,
  nsmall = 1L,
  decimal.mark = mid_dot()
)
```

Arguments

x	[num] numeric value
metric	[chr: default 'prop' c('prop', 'pp', 'count', rate)]
digits	[integer: default 1L] passed to ‘round()’
nsmall	[integer: default 1L] passed to ‘format()’
decimal.mark	[chr: default mid_dot()] decimal mark passed to ‘format()’

Value

[chr] formatted string

See Also

Other vector_formats: [add_epsilon\(\)](#), [fmt_magnitude\(\)](#), [format_oxford_comma\(\)](#), [fround\(\)](#), [fround_count_rate\(\)](#), [fround_metric\(\)](#), [fround_props\(\)](#)

Examples

```
fround_metric_lancet(0.123456789)
fround_metric_lancet(0.123456789, 'pp', 3, 4)
fround_metric_lancet(c(55.8346, 123.456789), 'count', 3, 4, ".")
```

`get_metrics`*Get metrics*

Description

Centrally managed definition for all allowed metrics.

Usage

```
get_metrics()
```

Value

[chr] vector of allowed metrics

See Also

Other metrics: [get_metric_labels\(\)](#)

Examples

```
get_metrics()
```

`get_metric_labels`*Get metric labels*

Description

Centrally managed definition for all metric labels.

Usage

```
get_metric_labels(metric)
```

Arguments

metric [chr]

Value

[list] named list of metric labels

See Also

Other metrics: [get_metrics\(\)](#)

Examples

```
get_metric_labels('prop')
```

get_style	<i>Get a style from the styles dictionary</i>
-----------	---

Description

Accessor function to retrieve a style from the package's styles dictionary.

Usage

```
get_style(style_name)
```

Arguments

style_name [chr] name of the style to retrieve

Value

[list] the requested style as a named list

See Also

Other styles: [assert_style_schema\(\)](#), [get_style_schema\(\)](#), [new_style\(\)](#), [set_style\(\)](#), [style_lancet\(\)](#), [style_nature\(\)](#)

Examples

```
get_style("lancet")
```

get_style_schema	<i>Get style schema</i>
------------------	-------------------------

Description

Centrally managed definition for all required journal format styles.

Usage

```
get_style_schema()
```

Value

[list] named list of style elements and their expected types

See Also

Other styles: [assert_style_schema\(\)](#), [get_style\(\)](#), [new_style\(\)](#), [set_style\(\)](#), [style_lancet\(\)](#), [style_nature\(\)](#)

Examples

```
get_style_schema()
```

mid_dot	<i>Mid-dot</i>
---------	----------------

Description

Lancet numeric decimal standard: "." ("U00B7")

Usage

```
mid_dot()
```

Value

[chr] mid-dot character

See Also

Other marks: [en_dash\(\)](#), [thin_space\(\)](#)

Examples

```
mid_dot()
```

new_style	<i>Make a new style by args</i>
-----------	---------------------------------

Description

Wrapper function to create and set a new style in one step.

Usage

```
new_style(
  style_name,
  prop_digits_round = 1,
  prop_nsmall = 1,
  count_method = "sigfig",
  count_digits_sigfig = 3,
  count_pad_sigfigs = TRUE,
  count_nsmall = 1,
  count_big.mark = ",",
  count_label_thousands = FALSE,
  rate_method = "sigfig",
  rate_digits_sigfig = 3,
  rate_pad_sigfigs = TRUE,
  rate_nsmall = 1,
  decimal.mark = ".",
  neg_mark_mean = "-",
  neg_mark_UI = "-",
  UI_only = FALSE,
  UI_text = "",
  assert_clu_order = TRUE,
  is_lancet = FALSE,
  round_5_up = TRUE
)
```

Arguments

style_name	[chr] name of the style to set
prop_digits_round	[int: default 1] number of digits to round proportions to
prop_nsmall	[int: default 1] minimum number of digits to the right of the decimal point - proportions
count_method	[chr: c("sigfig", "decimal", "int")] choose how to report counts - prioritize sigfigs across mean/lower/upper, hard-set decimals, or leave numbers in integer space.
count_digits_sigfig	[int: default 3] number of significant figures for counts

count_pad_sigfigs	[lgl: default TRUE] signif(5.00, 3) is "5" - do you want to pad the trailing 0s back on - usually TRUE?
count_nsmall	[int: default 1] passed to 'format()' if 'count_method' == 'decimal'
count_big.mark	[chr: default ","] character to use for counts thousand, million, billion separator e.g. ","
count_label_thousands	[lgl: default FALSE] whether format counts as e.g. 10,000 as '10 thousand'
rate_method	[chr: c("sigfig", "decimal", "int")] choose how to report rates - prioritize sigfigs across mean/lower/upper, hard-set decimals, or leave numbers in integer space.
rate_digits_sigfig	[int: default 3] number of significant figures for rates
rate_pad_sigfigs	[lgl: default TRUE] signif(5.00, 3) is "5" - do you want to pad the trailing 0s back on for rates - usually TRUE?
rate_nsmall	[int: default 1] passed to 'format()' if 'rate_method' == 'decimal'
decimal.mark	[chr: default "."] decimal mark e.g. "." or 'mid_dot()' for Lancet.
neg_mark_mean	[chr: default "-"] string to describe central value negatives - e.g. "-1 (-2 to 4)" could become "Negative 1 (-2 to 4)"
neg_mark_UI	[chr: default "-"] string to describe negative sign in UI brackets e.g. "1 (-2 to 4)" could become "1 (-2 to 4)" (en-dash)
UI_only	[lgl: default FALSE] Return only UI from 'format_journal_df()' family functions?
UI_text	[chr: default ""] Text to appear inside UI brackets before numbers e.g. "2 (1 - 4)" could become "2 (95%UI 1 - 4)"
assert_clu_order	[lgl: default TRUE] whether to assert CLU relationships (ensure lower < central < upper)
is_lancet	[lgl: default FALSE] TRUE to handle edge-case Lancet count formatting policies
round_5_up	[lgl: default TRUE] In R, 'round(1245, 3)' is "1240". Do you want to round to "1250" instead? Default TRUE to conform with common expectations.

Value

[chr] invisible vector of input objects

See Also

Other styles: [assert_style_schema\(\)](#), [get_style\(\)](#), [get_style_schema\(\)](#), [set_style\(\)](#), [style_lancet\(\)](#), [style_nature\(\)](#)

Other styled_formats: [format_journal_clu\(\)](#), [format_journal_df\(\)](#), [format_lancet_clu\(\)](#), [format_lancet_df\(\)](#), [format_metric_cols\(\)](#), [format_nature_clu\(\)](#), [format_nature_df\(\)](#), [fround_clu_triplet\(\)](#)

Examples

```
new_style(style_name = "my_style")
```

set_magnitude	<i>Define magnitude, magnitude label and denominator for a vector of numeric values</i>
---------------	---

Description

Support function used on `_central_` (e.g. mean) values for later formatting. Routes to appropriate helper based on metric.

Usage

```
set_magnitude(
  x,
  metric,
  mag = NULL,
  count_label_thousands = FALSE,
  verbose = TRUE
)
```

Arguments

x	[num] numeric vector
metric	[chr] metric: "prop", "pp", "count", "rate" (required)
mag	[chr: default NULL] magnitude override (NULL = auto-detect) - For counts: "t", "m", "b" - For rates: "per10", "per100", "per1k", ..., "per10b" - For props/pp: "as-is" (no scaling, use values as provided)
count_label_thousands	[lgl: default FALSE] allow "thousands" magnitude for counts? Not Lancet-valid.
verbose	[lgl: default TRUE] show warnings?

Value

[data.frame] with columns: mag, mag_label, denom

See Also

Other magnitudes: [fmt_magnitude\(\)](#), [set_magnitude_count\(\)](#), [set_magnitude_prop\(\)](#), [set_magnitude_rate\(\)](#)

Examples

```
# Proportions (no scaling)
set_magnitude(c(0.5, 0.75), metric = "prop")

# Counts
set_magnitude(c(1e3, 1e6, 1e9), metric = "count")

# Rates
set_magnitude(c(0.0000123, 0.0000456), metric = "rate")
```

<code>set_style</code>	<i>Set a new style by list</i>
------------------------	--------------------------------

Description

Set a new style by list

Usage

```
set_style(style_name, style_entry)
```

Arguments

`style_name` [chr] name of the style to set
`style_entry` [list] named list representing the style entry

Value

[chr] invisible vector of input objects, to allow easier un-locking

See Also

Other styles: [assert_style_schema\(\)](#), [get_style\(\)](#), [get_style_schema\(\)](#), [new_style\(\)](#), [style_lancet\(\)](#), [style_nature\(\)](#)

Examples

```
set_style(
  style_name = "my_style"
, style_entry = list(
  style_name = "my_style"
, prop_digits_round = 1
, prop_nsmall = 1
, count_method = "sigfig"
, count_digits_sigfig = 3
, count_pad_sigfigs = TRUE
, count_nsmall = 1
, count_big.mark = ","
, count_label_thousands = FALSE
```

```
    , rate_method          = "sigfig"  
    , rate_digits_sigfig  = 3  
    , rate_pad_sigfigs    = TRUE  
    , rate_nsmall         = 1  
    , decimal.mark        = "."  
    , neg_mark_mean       = "-"  
    , neg_mark_UI         = "-"  
    , UI_only              = FALSE  
    , UI_text              = ""  
    , assert_clu_order    = TRUE  
    , is_lancet            = FALSE  
    , round_5_up          = TRUE  
  )  
)
```

style_lancet

Lancet style schema

Description

Pre-defined style schema for Lancet journal formatting

Usage

```
style_lancet()
```

Value

[list] named list representing the lancet style

See Also

Other styles: [assert_style_schema\(\)](#), [get_style\(\)](#), [get_style_schema\(\)](#), [new_style\(\)](#), [set_style\(\)](#), [style_nature\(\)](#)

Examples

```
style_lancet()
```

style_nature	<i>Nature style schema</i>
--------------	----------------------------

Description

The default style for the package.

Usage

```
style_nature()
```

Details

Pre-defined style schema for Nature journal formatting.

Value

[list] named list representing the nature style

See Also

Other styles: [assert_style_schema\(\)](#), [get_style\(\)](#), [get_style_schema\(\)](#), [new_style\(\)](#), [set_style\(\)](#), [style_lancet\(\)](#)

Examples

```
style_nature()
```

thin_space	<i>Thin space</i>
------------	-------------------

Description

Lancet thin space separator for counts 10,000 – 999,9999 instead of comma ",": ("U2009")

Usage

```
thin_space()
```

Value

[chr] thin space character

See Also

Other marks: [en_dash\(\)](#), [mid_dot\(\)](#)

thin_space

25

Examples

```
thin_space()
```

Index

- * **magnitudes**
 - fmt_magnitude, 3
 - set_magnitude, 21
- * **marks**
 - en_dash, 2
 - mid_dot, 18
 - thin_space, 24
- * **metrics**
 - get_metric_labels, 16
 - get_metrics, 16
- * **styled_formats**
 - format_journal_clu, 4
 - format_journal_df, 5
 - format_lancet_clu, 7
 - format_lancet_df, 8
 - format_metric_cols, 9
 - format_nature_clu, 10
 - format_nature_df, 11
 - new_style, 19
- * **styles**
 - get_style, 17
 - get_style_schema, 18
 - new_style, 19
 - set_style, 22
 - style_lancet, 23
 - style_nature, 24
- * **vector_formats**
 - fmt_magnitude, 3
 - format_oxford_comma, 13
 - fround, 13
 - fround_metric, 14
 - fround_metric_lancet, 15
 - format_journal_df, 5, 5, 7, 9–12, 20
 - format_lancet_clu, 5, 6, 7, 9–12, 20
 - format_lancet_df, 5–7, 8, 10–12, 20
 - format_metric_cols, 5–7, 9, 9, 11, 12, 20
 - format_nature_clu, 5–7, 9, 10, 10, 12, 20
 - format_nature_df, 5–7, 9–11, 11, 20
 - format_oxford_comma, 4, 13, 14, 15
 - fround, 4, 13, 13, 15
 - fround_clu_triplet, 5–7, 9–12, 20
 - fround_count_rate, 4, 13–15
 - fround_metric, 4, 13, 14, 14, 15
 - fround_metric_lancet, 4, 13–15, 15
 - fround_props, 4, 13–15
 - get_metric_labels, 16, 16
 - get_metrics, 16, 17
 - get_style, 17, 18, 20, 22–24
 - get_style_schema, 17, 18, 20, 22–24
 - mid_dot, 2, 18, 24
 - new_style, 5–7, 9–12, 17, 18, 19, 22–24
 - set_magnitude, 4, 21
 - set_magnitude_count, 4, 21
 - set_magnitude_prop, 4, 21
 - set_magnitude_rate, 4, 21
 - set_style, 17, 18, 20, 22, 23, 24
 - style_lancet, 17, 18, 20, 22, 23, 24
 - style_nature, 17, 18, 20, 22, 23, 24
 - thin_space, 2, 18, 24
- add_epsilon, 4, 13–15
- assert_style_schema, 17, 18, 20, 22–24
- en_dash, 2, 18, 24
- fmt_magnitude, 3, 13–15, 21
- format_journal_clu, 4, 6, 7, 9–12, 20